ProLite E2410HDSD-1

The new ProLite E2410HDSD-1 is the new 24” screen size to join the iiyama Eco-monitor range. Energy Star rated and using less than 1W in power management mode it is good for the environment yet still features the high specification you come to expect from iiyama. Combining an exceptionally fast 2ms response time, true 16:9 HD and 1920x1080 (2.1mega pixel) native resolution makes for improved colour range and depth in gaming and video and graphic applications. The E2410HDSD features 2 x 2W speakers and analogue and digital connectivity for flexibility across different platforms.

Panel	TN
Diagonal	24"
Display area h x w	298.9 x 531.4 mm; 11.8" x 20.9"
Response time	2 ms
Contrast	20 000 : 1 ACR
Contrast	1000 : 1 typical
Brightness	250 cd/m² typical
Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80°
Display colour	16.7 million
Pixel pitch h x v	0.277 x 0.277 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Analog input connector	D-Sub
Digital input connector	DVI-D
HDCP	yes
Output connector	headphone connector
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 2 W (Stereo)
Included accessories	power cable, D-Sub cable, DVI-D cable, audio cable, stand, stand-base, quick start guide, safety guide
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 9 languages (EN, DE, FR, ES, IT, PT, Chinese, RU, JP) and 5 front controls (Power, Menu/ Select, +/ Volume, -/ ECO, Auto)
User controls	luminance (contrast, brightness, ECO, picture mode, ACR), image setup (clock, phase, H. position, V. position, aspect), colour adjust (colour temperature, gamma), OSD setup (H. position, V. position , time out, language), others (reset, signal select, OD, information), volume, auto adjust
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7
Ergonomics	TCO 5.0, CE, TÜV-Bauart
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	25 W typical; max. 1 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	566 x 395 x 190 mm
Weight	4.4 kg
Aspect ratio	16 : 9

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.